

DATE: 02/11/2005
MANUFACTURER'S NAME: Walter G. Legge Co., Inc.
STREET ADDRESS: 444 Central Ave., Peekskill, NY 10566
EMERGENCY TELEPHONE: CHEMTREC 800-424-9300
INFORMATION NUMBER: 914-737-5040
TRADE NAME: CONDUCTIVE CLEANER
DOT HAZARD CLASS: NOT Applicable

SECTION II - HAZARDOUS INGREDIENTS

CAS NUMBER	CHEMICAL NAME	OSHA PEL	ACGIH TLV
------------	---------------	----------	-----------

NO REPORTABLE HAZARDOUS INGREDIENTS

TSCA: This material or its components are listed on the TSCA Chemical Substance Inventory and is in compliance will all applicable rules and orders.

SECTION III - PHYSICAL DATA

BOILING POINT: 212 DEGREES F	VAPOR DENSITY: LIGHTER THAN AIR
WEIGHT PER GALLON: 8.4	VAPOR PRESSURE: NE
SOLUBILITY IN WATER: COMPLETE	APPEARANCE: GREEN LIQUID
DOT CATEGORY: NON-REGULATED	FLASH POINT: NE
EVAPORATION RATE: SLOWER THAN ETHER	ODOR: CITRUS

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

EXTINGUISHING MEDIA: NONE REQUIRED
UNUSUAL FIRE AND EXPLOSION HAZARDS: NONE
SPECIAL FIRE FIGHTING PROCEDURES: Water may be used to cool down unopened containers in vicinity. As in any fire, prevent human exposure to fire, smoke, fumes or products of combustion. Evacuate non-essential personnel from the fire area. Fire fighters should wear OSHA approved self-contained breathing apparatus and full protection clothing.

SECTION V - HEALTH HAZARD DATA

***HMIS RATING: HEALTH-1; FLAMMABILITY-0; REACTIVITY-0

THRESHOLD LIMIT VALUE: See Section II

EFFECTS OF OVEREXPOSURE: ACUTE: Irritation of eyes and skin may occur with overexposure. Continued breathing of vapors may irritate respiratory tract causing headache, nausea and dizziness.

CHRONIC: Unknown

EMERGENCY FIRST AID PROCEDURES:

INHALATION: Remove to fresh air. Restore respiration if necessary. Treat symptomatically.

EYE CONTACT: Flush immediately with copious quantities of water for 15 minutes minimum. Consult a physician.

DERMAL CONTACT: Wash affected areas with soap and water. Remove contaminated clothing. Consult physician if irritation persists.

INGESTION: Drink 1 or 2 glasses of water to dilute. DO NOT INDUCE VOMITING. If spontaneous vomiting occurs keep head at or below knee level to prevent aspiration into lungs. Consult physician or poison control center immediately.

PRIMARY ROUTES OF ENTRY: Inhalation and dermal contact.

SECTION VI - REACTIVITY DATA

STABILITY: Stable

CONDITIONS TO AVOID: Protect from freezing.

INCOMPATIBILITY (Materials to avoid): Any material that reacts with water.

HAZARDOUS DECOMPOSITION PRODUCTS: May produce hazardous fumes when heated.

HAZARDOUS POLYMERIZATION: Will not occur.

SECTION VII - SPILL AND LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Wear appropriate personal protection equipment and approved respirator. Contain spill with absorbent material and put into vapor tight containers. Clean up spills thoroughly as residue is slippery.

WASTE DISPOSAL: Dispose of in accordance with Federal, State, and local regulations.

SECTION VIII - SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: In outdoor or open areas, use NIOSH/MSHA approved organic vapor cartridge type respirator to remove solid airborne particles of over spray during spray application. In restricted ventilation areas use NIOSH/OSHA approved organic vapor cartridge type respirator designed to remove a combination of particles and vapor.

VENTILATION: In confined spaces mechanical ventilation is required to keep the air contaminant concentration below current applicable OSHA permissible exposure units.

