

DATE: May 2, 2005  
 MANUFACTURER'S NAME: Walter G Legge Co., Inc.  
 STREET ADDRESS: 444 Central Ave Peekskill, NY 10566-2003  
 EMERGENCY TELEPHONE: CHEMTREC 800-424-9300  
 INFORMATION NUMBER : 914-737-5040  
 PRODUCT CLASS: ACRYLIC EMULSION  
 TRADE NAME: ELIMSTAT LX

\*\*\*\*\*  
 SECTION II - HAZARDOUS INGREDIENTS  
 \*\*\*\*\*

INGREDIENTS	*% BY WT*	OEL	*LEL*	VAPOR PRESSURE
TITANIUM DIOXIDE	* 8 %	*10mg/m3 ACGIH-TLV*	- *	-
(AS NUISANCE DUST) *		*15mg/m3 OSHA-PEL *	* *	
CAS # 13463-67-7	*	*	* *	
CALCIUM CARBONATE	* 1 %	*10mg/m3 ACGIH-TLV*	- *	-
(AS NUISANCE DUST) *		*	* *	
CAS # 1317-65-3	*	*	* *	
ALUMINUM SILICATE	* 1 %	*10mg/m3 ACGIH-TLV*	- *	-
(AS NUISANCE DUST) *		* ACGIH/OSHA *	* *	
CAS # 1318-74-7	*	*	* *	

\*\*\*\*\*  
 SECTION III - PHYSICAL DATA  
 \*\*\*\*\*

BOILING POINT: 212 DEGREES F                      VAPOR DENSITY: LIGHTER THAN AIR  
 EVAPORATION RATE: SLOWER THAN ETHER    % VOLATILE: 61-64 %  
 WEIGHT PER GALLON: 9.98                      VOC RATE: LESS THAN .7 LBS/GAL  
 SPECIFIC GRAVITY: 1.235

\*\*\*\*\*  
 SECTION IV - FIRE AND EXPLOSION HAZARD DATA  
 \*\*\*\*\*

DOT CATEGORY: NON-REGULATED                      FLASH POINT: UNDETECTED  
 LEL: SEE SECTION II                      EXTINGUISHING MEDIA: NONE REQUIRED  
 UNUSUAL FIRE AND EXPLOSION HAZARDS: NONE  
 SPECIAL FIRE FIGHTING PROCEDURES : Water may be used to cool down  
 unopened containers in vicinity. Fire fighters should wear OSHA  
 approved self-contained breathing apparatus and full protective  
 clothing.

\*\*\*\*\*

SECTION V - HEALTH HAZARD DATA

\*\*\*\*\*

HMIS RATING: HEALTH-1; FLAMMABILITY-0; REACTIVITY-0 THRESHOLD  
LIMIT VALUE: See Section II

EFFECTS OF OVEREXPOSURE:

ACUTE: Irritation of eyes and skin may occur with overexposure.  
Continued breathing of vapors may irritate respiratory tract  
causing headache, nausea and dizziness.

CHRONIC: Unknown

EMERGENCY FIRST AID PROCEDURES:

INHALATION: Remove to fresh air. Restore respiration if necessary.  
Treat symptomatically.

EYE CONTACT: Flush immediately with copious quantities of water for  
15 minutes minimum. Consult a physician.

DERMAL CONTACT: Wash affected areas with soap and water. Remove  
contaminated clothing. Consult physician if irritation persists.

INGESTION: Drink 1 or 2 glasses of water to dilute. DO NOT  
INDUCEVOMITING. If spontaneous vomiting occurs keep head at or  
below knee level to prevent aspiration into lungs. Consult  
physician of poison control center immediately.

PRIMARY ROUTES OF ENTRY: Inhalation and dermal contact.

\*\*\*\*\*

SECTION VI - REACTIVITY DATA

\*\*\*\*\*

STABILITY: Stable CONDITIONS TO AVOID:

INCOMPATIBILITY (Materials to avoid): Protect from freezing.

Any material that reacts with water.

HAZARDOUS DECOMPOSITION PRODUCTS: May produce hazardous fumes when  
heated.

HAZARDOUS POLYMERIZATION: Will not occur.

\*\*\*\*\*

SECTION VII - SPILL AND LEAK PROCEDURES

\*\*\*\*\*

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Eliminate all ignition sources. Wear appropriate personal  
protection equipment and approved respirator. Contain spill with  
absorbent material and put into vapor tight containers. Prevent  
material from contacting and water sources or sewers leading to  
surface waters.

WASTE DISPOSAL: Dispose of in accordance with Federal, State, and  
local regulations.

\*\*\*\*\*

SECTION VIII - SPECIAL PROTECTION INFORMATION

\*\*\*\*\*

RESPIRATORY PROTECTION: In outdoor or open areas, use NIOSH/MSHA  
approved organic vapor cartridge type respirator to remove solid

airborne particles of over spray during spray application. In restricted ventilation areas use NIOSH/MSHA approved organic vapor cartridge type respirator designed to remove a combination of particles and vapor.

VENTILATION: In confined spaces mechanical ventilation is required to keep the air contaminant concentration below current applicable OSHA permissible exposure units.

PROTECTIVE GLOVES: Impervious type required for long or repeated exposure.

EYE PROTECTION: Use safety eye wear to protect against splash of liquids.

OTHER PROTECTIVE EQUIPMENT: Prevent prolonged skin contact with contaminated clothing.

HYGIENIC PRACTICES: Wash hands before eating, smoking or using washroom facilities.

\*\*\*\*\*  
SECTION IX - SPECIAL PRECAUTIONS

\*\*\*\*\*  
PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Store in compliance with good housekeeping procedures. Protect from freezing, and extreme heat. Store at temperatures above 45 degrees F.

OTHER PRECAUTIONS: Ground containers when pouring liquids and powders to avoid static charge buildup. Do not handle until manufacturers material safety data sheets have been read and understood. Provide adequate ventilation or respiratory protection to remove decomposition products during welding or flame cutting coated surfaces.

To the best of our knowledge, the information contained herein is accurate. However, Walter G LEGGE Co., Inc. assumes no liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we can not guarantee that these are the only hazards which exist.