

DATE: May 3, 2005
 MANUFACTURER NAME: Walter G Legge Co., Inc.
 STREET ADDRESS: 444 Central Ave Peekskill, NY 10566-2003
 EMERGENCY TELEPHONE: CHEMTREC 800-424-9300
 INFORMATION NUMBER : 914-737-5040
 PRODUCT CLASS: ACRYLIC EMULSION
 TRADE NAME: ELIMSTAT SDSC-549411

 SECTION II - HAZARDOUS INGREDIENTS

INGREDIENTS	*% BY WT*	OEL	*LEL*	VAPOR PRESSURE
TITANIUM DIOXIDE	* 13 %	*10mg/m3 ACGIH-TLV*	- *	-
(AS NUISANCE DUST)*		*15mg/m3 OSHA-PEL *	* *	
CAS # 13463-67-7	*	*	* *	
CALCIUM CARBONATE	* 1 %	*10mg/m3 ACGIH-TLV*	- *	-
(AS NUISANCE DUST)*		*	* *	
CAS # 1317-65-3	*	*	* *	
	*	*	* *	

Material regulated under SARA Title III, Section 313

 SECTION III - PHYSICAL DATA

BOILING POINT: 212 - 490°F VAPOR DENSITY: HEAVIER THAN AIR
 EVAPORATION RATE: SLOWER THAN ETHER % VOLATILE by Weight: 39%
 WEIGHT PER GALLON: 12.7 lbs VOC RATE: LESS THAN .6
 LBS/GAL

 SECTION IV - FIRE AND EXPLOSION HAZARD DATA

DOT CATEGORY: NON-REGULATED FLASH POINT: NONE DETECTED
 LEL: SEE SECTION II
 EXTINGUISHING MEDIA: NONE REQUIRED
 UNUSUAL FIRE AND EXPLOSION HAZARDS: NONE
 SPECIAL FIRE FIGHTING PROCEDURES : Water may be used to cool down
 unopened containers in vicinity. Firefighters should wear OSHA
 approved self-contained breathing apparatus and full protective
 clothing.

vapor cartridge type respirator designed to remove a combination of particles and vapor.

VENTILATION: In confined spaces mechanical ventilation is required to keep the air contaminant concentration below current applicable OSHA permissible exposure units.

PROTECTIVE GLOVES: Impervious type required for long or repeated exposure.

EYE PROTECTION: Use safety eye wear to protect against splash of liquids. OTHER PROTECTIVE EQUIPMENT: Prevent prolonged skin contact with contaminated clothing.

HYGIENIC PRACTICES: Wash hands before eating, smoking or using washroom facilities.

SECTION IX - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Store in compliance with good housekeeping procedures. Protect from freezing, and extreme heat. Store at temperatures above 45°F. OTHER PRECAUTIONS: Ground containers when pouring liquids and powders to avoid static charge buildup. Do not handle until manufacturers material safety data sheets have been read and understood. Provide adequate ventilation or respiratory protection to remove decomposition products during welding or flame cutting coated surfaces.

To the best of our knowledge, the information contained herein is accurate. However, Walter G LEGGE Co., Inc. assumes no liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.