

DATE: May 3, 2005
 MANUFACTURER NAME: Walter G Legge Co., Inc.
 STREET ADDRESS: 444 Central Ave Peekskill, NY 10566-2003
 EMERGENCY TELEPHONE: CHEMTREC 800-424-9300
 INFORMATION NUMBER : 914-737-5040
 PRODUCT CLASS: ACRYLIC EMULSION
 TRADE NAME: ELIMSTAT SDSC-77203

SECTION II - HAZARDOUS INGREDIENTS

INGREDIENTS	*% BY WT *	OEL	*LEL*	VAPOR PRESSURE	mmHg-20C
TITANIUM DIOXIDE (AS NUISANCE DUST) CAS # 13463-67-7	* 13 % * *	*10mg/m3 ACGIH-TLV* * *	- * *	* * *	- * *
CALCIUM CARBONATE (AS NUISANCE DUST) CAS # 1317-65-3 * * * *	* 1 % * * * *	*10mg/m3 ACGIH-TLV* * * * *	- * * * *	* * * * *	- * * * *

Material regulated under SARA Title III, Section 313

SECTION III - PHYSICAL DATA

BOILING POINT: 212 - 490 F VAPOR DENSITY: HEAVIER THAN AIR
 EVAPORATION RATE: SLOWER THAN ETHER % VOLATILE by Weight: 39%
 WEIGHT PER GALLON: 12.7 lbs VOC RATE: LESS THAN .6 LBS/GAL

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

DOT CATEGORY: NON-REGULATED FLASH POINT: NONE DETECTED
 LEL: SEE SECTION II
 EXTINGUISHING MEDIA: NONE REQUIRED
 UNUSUAL FIRE AND EXPLOSION HAZARDS: NONE
 SPECIAL FIRE FIGHTING PROCEDURES: Water may be used to cool down unopened
 containers in vicinity. Firefighters should wear OSHA approved self-contained breathing

apparatus and full protective clothing.

SECTION V - HEALTH HAZARD DATA

HMIS RATING HEALTH - 1 FLAMMABILITY - 0 REACTIVITY - 0

THRESHOLD LIMIT VALUE: See Section II

EFFECTS OF OVEREXPOSURE: ACUTE: Irritation of eyes and skin may occur with overexposure. Continued breathing of vapors may irritate respiratory tract causing headache, nausea and dizziness.

CHRONIC: None known.

EMERGENCY FIRST AID PROCEDURES:

INHALATION: Remove to fresh air. Restore respiration if necessary. Treat symptomatically.

EYE CONTACT: Flush immediately with copious quantities of water for 15 minutes minimum. Consult a physician.

DERMAL CONTACT: Wash affected areas with soap and water. Remove contaminated clothing. Consult physician if irritation persists.

INGESTION: Drink 1 or 2 glasses of water to dilute. DO NOT INDUCE VOMITING. If spontaneous vomiting occurs keep head at or below knee level to prevent aspiration into lungs. Consult physician of poison control center immediately.

PRIMARY ROUTES OF ENTRY: Inhalation and dermal contact.

SECTION VI - REACTIVITY DATA

STABILITY: Stable CONDITIONS TO AVOID:

INCOMPATIBILITY (Materials to avoid): Protect from freezing.

Any material that reacts with water.

HAZARDOUS DECOMPOSITION PRODUCTS: May produce hazardous fumes when heated.

HAZARDOUS POLYMERIZATION: Will not occur.

SECTION VII - SPILL AND LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Eliminate all ignition sources. Wear appropriate personal protection equipment and approved respirator. Contain spill with absorbent material and put into vapor tight containers. Prevent material from contacting and water sources or sewers leading to surface waters.

WASTE DISPOSAL: Dispose of in accordance with Federal, State, and local regulations.

SECTION VIII - SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: In outdoor or open areas, use NIOSH/MSHA approved organic vapor cartridge type respirator to remove solid airborne particles of over spray during spray application. In restricted ventilation areas use NIOSH/MSHA approved organic vapor cartridge type respirator designed to remove a combination of particles and vapor.

VENTILATION: In confined spaces mechanical ventilation is required to keep the air contaminant concentration below current applicable OSHA permissible exposure units.

PROTECTIVE GLOVES: Impervious type required for long or repeated exposure.

EYE PROTECTION: Use safety eye wear to protect against splash of liquids. OTHER

PROTECTIVE EQUIPMENT: Prevent prolonged skin contact with contaminated clothing.

HYGIENIC PRACTICES: Wash hands before eating, smoking or using washroom facilities.

SECTION IX - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Store in compliance with good housekeeping procedures. Protect from freezing and extreme heat. Store at temperatures above 45 degrees F.

OTHER PRECAUTIONS: Ground containers when pouring liquids and powders to avoid static charge buildup. Do not handle until manufacturers material safety data sheets have been read and understood. Provide adequate ventilation or respiratory protection to remove decomposition products during welding or flame cutting coated surfaces.

To the best of our knowledge, the information contained herein is accurate. However, Walter G LEGGE Co., Inc. assumes no liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.