

**DATE:** 3 May 2005  
**MANUFACTURER'S NAME:** WALTER G. LEGGE CO., INC.  
**ADDRESS:** 444 CENTRAL AVE., PEEKSKILL, NY 10566  
**INFORMATION TELEPHONE:** 914-737-5040  
**CHEMTREC:** 800-424-9300  
**TRADE NAME:** ELIMSTAT UXM 60P  
**PRODUCT CLASS:** WATER BORNE URETHANE COATING  
**STOCK #** K4091

.....  
**SECTION II - HAZARDOUS INGREDIENTS**

<b>INGREDIENTS</b>	<b>ACGIH/TLV OSHA/PEL</b>
CONDUCTIVE AGENT (PROPRIETARY)	5mg/m <sup>3</sup>
CAS # MIXTURE	
SODIUM SILICONATE	2mg/m <sup>3</sup>
CAS # MIXTURE	

All other ingredients in this product are listed in the TSCA inventory and are not a hazardous chemical as defined by OSHA Standard 29 CFR 1910.1200.

\*\*\*\*\*

**SECTION III - PHYSICAL DATA**

**BOILING POINT:** 212 TO 490 Degrees F  
**VAPOR DENSITY:** Lighter than air  
**EVAPORATION RATE:** Slower than ether  
**PERCENT SOLID:** 44 - 46%  
**VOC RATE:** Less than .7 Ibs/gal.  
**pH:** 9.04  
**SPECIFIC GRAVITY:** 1.05  
**WEIGHT PER GALLON:** 8.82 Pounds  
**VISCOSITY:** 440 cps



\*\*\*\*\*

SECTION VI - REACTIVITY DATA

\*\*\*\*\*

STABILITY: Stable

CONDITIONS TO AVOID: Protect from freezing.

INCOMPATIBILITY (Materials to avoid):

Any material that reacts with water, keep away from salts and anionic materials which may coagulate product.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon Dioxide and Carbon Monoxide.

HAZARDOUS POLYMERIZATION: Will not occur.

\*\*\*\*\*

SECTION VII - SPILL AND LEAK PROCEDURES

\*\*\*\*\*

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Eliminate all ignition sources. Wear appropriate personal protection equipment and approved respirator. Contain spill with absorbent material and put into vapor tight containers. Prevent material from contacting any water sources or sewers leading to surface waters.

WASTE DISPOSAL: Dispose of in accordance with Federal, State, and local regulations.

\*\*\*\*\*

SECTION VIII - SPECIAL PROTECTION INFORMATION

\*\*\*\*\*

RESPIRATORY PROTECTION: In outdoor or open areas, use NIOSH/MSHA approved organic vapor cartridge type respirator to remove solid airborne particles of over spray during spray application. In restricted ventilation areas use NIOSH/MSHA approved organic vapor cartridge type respirator designed to remove a combination of particles and vapor. VENTILATION: In confined spaces mechanical ventilation is required to keep the air contaminant concentration below current applicable OSHA permissible exposure units.

PROTECTIVE GLOVES: Impervious type required for long or repeated exposure.

EYE PROTECTION: Use safety eye wear to protect against splash of liquids.

OTHER PROTECTIVE EQUIPMENT: Prevent prolonged skin contact with contaminated clothing.

HYGIENIC PRACTICES: Wash hands before eating, smoking or using washroom facilities.

\*\*\*\*\*

SECTION IX - SPECIAL PRECAUTIONS

\*\*\*\*\*

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Store in compliance with good housekeeping procedures. Protect from freezing, and extreme heat. Store at temperatures between 40 and 120° F.

OTHER PRECAUTIONS: Ground containers when pouring liquids and powders to avoid static charge buildup. Do not handle until manufacturers material safety data sheets have been read and understood. Provide adequate ventilation or respiratory protection to remove decomposition products during welding or flame cutting coated surfaces.

To the best of our knowledge, the information contained herein is accurate. However, Walter G LEGGE Co., Inc. assumes no liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we can not guarantee that these are the only hazards which exist.